



1-800-283-6266

phone: (713) 466-1449

email: customerservice@enconsafety.com

# PEDESTAL FACEWASH w/ STAINLESS STEEL BOWL & STAINLESS STEEL COVER PART NUMBER: 01045509SBC

## SPECIFICATION:

Third party certified to ANSI Z358.1, the eye/facewash shall deliver 8.0 gpm (30.3 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with stainless steel (SS) single motion activation stay open ball valves with SS balls. Eye/Facewash shall include stainless steel (SS) actuator with actuation graphic, 7"x 11" (17.8 cm X 27.9 cm) sign, ½" type 304 schedule 40 stainless steel piping, schedule 40 stainless steel pedestal mount/drain for free-standing installation. Facewash heads to be manufactured of UV resistant ABS plastic mounted on a chrome plated brass wye. The bowl is a type 304 SS and includes a stainless steel cover to inhibit dust and/or particulate accumulation on the eye/face wash heads when not in use. The cover shall open immediately on actuation of the eye/face wash valve and will be able to be opened or closed manually, separate of the eye/face wash actuator, to allow for ease of maintenance of the eye/face wash nozzle assembly under the bowl cover. Unit shall be supplied with a non-deteriorating Stainless steel screen/filter. Eye/Facewash units with deterioration screens/filters are not acceptable.

Encon Safety Products Model 01045509SBC includes pedestal mount facewash with stainless steel bowl and stainless steel bowl cover.

**\*Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

## MATERIALS OF CONSTRUCTION:

**PIPING:** Type 304 schedule 40 stainless steel.

**VALVES:** ½" Stainless steel stay open ball valves with S/S balls, stainless steel push plate with actuation graphic.

**EYE/FACEWASH HEAD:** ABS plastic dual stream head with chrome plated brass wye.

**BOWL AND COVER:** Type 304 stainless steel.

**REGULATOR:** Self-adjusting 8.0 gpm (30.3 lpm).

**SUPPLY:** ½" NPT

**WASTE:** 1 ¼" NPT

**WEIGHT:** 27 lbs (12.24 kgs)

