

**Encon<sup>®</sup>**  
**SAFETY PRODUCTS**  
**1-800-283-6266**  
 phone: (713) 466-1449  
 email: customerservice@enconsafety.com

# VERTICAL SHOWER

## PART NUMBER: 01053002

**SPECIFICATION:**

Third party certified to ANSI Z358.1, the shower shall deliver 30 gpm (113.6 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Shower shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with 1 1/4" chrome plated (CP) bronze single motion activation stay open ball valve with CP ball, SS actuator with actuation graphic, CP brass piping and 1 1/4" supply connection. Shower head shall be supplied with self-adjusting 30 gpm (113.6 lpm) regulator to assure constant flow and pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Shower head to be manufactured of UV resistant high visibility yellow ABS plastic. Shower head must deliver a minimum of 20" (50.8 cm) diameter pattern to the target area 60" (152.4 cm) above standing level. Shower units that provide improper flow pattern are not acceptable.

**Encon Safety Products Model 01053002** includes vertical shower unit.

**Encon Safety Products Model 01053005** includes vertical shower unit with stainless steel valve.

**Encon Safety Products Model 01053002SS** includes vertical shower unit with 304 SS shower head.

**\*Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

**MATERIALS OF CONSTRUCTION:**

**PIPING:** Chrome plated brass.

**VALVES:** 1 1/4" chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless pull rod assembly with actuation graphic.

**SHOWERHEAD:** Yellow ABS plastic shower head. Option: Type 304 stainless steel shower head.

**REGULATOR:** Self-adjusting 30 gpm (113.6 lpm) regulator.

**SUPPLY:** 1 1/4" NPT

**WEIGHT:** 11 lbs (4.98 kgs)

